

Aqua Pro

Perfect All-Purpose Sealer (Water-Based).

- V.O.C. Compliant
- Penetrates Like a Solvent and Evaporates
- Protects Your Stone from Water and Oil Stains
- Quick Dry, Low Odor
- Multi-Purpose Sealer

STONE PRO

866.786.6310

www.stoneproonline.com



Product Description: A water based impregnator sealer, which penetrates grout, stone and masonry surfaces to protect against water and oil staining while allowing substrate to properly breath. Non-yellowing and long-lasting. Will not change the appearance of your stone surface.

Coverage: Product will cover approximately 200 to 1,000 ft.² per gallon dependant on porosity of stone. Two coats are recommended for optimum performance. Cure time: 24 hrs. / repels water, 72 hrs. / fully cured.

Directions: Always test product in an inconspicuous area to test suitability for intended use. Surface must be sound, thoroughly clean and free from waxes, sealants or coatings of any kind. For best results, use Stone Pro's Formula 51 stripper before applying Aqua Pro. Apply product evenly using a low-pressure sprayer or lamb's wool applicator. Do not dilute in any way.

Caution: Combustible. Keep away from heat, open flame, sparks and/or any possible ignition source. Keep work well ventilated. Gloves and goggles should be worn at all times. Respirator suggested in larger areas or non-ventilated areas. Read directions and other cautions on back of container before use of this product.

SECTION I - PRODUCT IDENTIFICATION

TRADE NAME: Stone Pro Aqua Pro

PRODUCT CODE: AP

CHEMICAL NAME: Fluorochemical

CAS #: N/A mixture

DOT HAZARD CLASS: N/A

DATE: June 14, 2006

DOT SHIPPING NAME: Cleaning compound Non Hazardous

SECTION II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	CAS #	%	TLV (UNITS)	PEL
Isopropyl Alcohol	67-63-0	<6	400 ppm	400 ppm
Ethylene Glycol Monobutyl Ether	111-76-2	<6	25 ppm skin	25 ppm

SECTION III - PHYSICAL DATA

BOILING POINT: (F) 212

SOLUBILITY: 100%

pH: 7.8

PERCENT VOLATILE: ND

VAPOR DENSITY: ND

VAPOR PRESSURE: <30

EVAPORATION RATE (BUTYL ACETATE = 1): ND

SPECIFIC GRAVITY: 1.00

APPEARANCE & ODOR: Clear liquid mild odor.

SECTION IV - FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT: N/A

FLAMMABLE LIMITS: N/A

LOWER: N/A

UPPER: N/A

FIRE/EXPLOSION HAZARDS: None

EXTINGUISHING MEDIA: Foam, CO₂, dry chemical

FIRE FIGHTING PROCEDURES: Fire fighters should wear self-contained breathing apparatus and full protective clothing. Use water spray to cool nearby containers and structures exposed to fire.

SECTION V - HEALTH HAZARD INFORMATION

PERMISSIBLE EXPOSURE LEVEL: ND

EYES: Slight irritation

SKIN: None under normal conditions.

INHALATION: None under normal conditions.

INGESTION: Ingesting large quantities may cause nausea.

THIS MATERIAL IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA

HMIS HAZARD CLASS: Health = 0 Flammability = 0 Reactivity = 0 Other = NA

Ranking: 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme

FIRST AID

EYE CONTACT: Flush with water for 20 minutes lifting eyelids. Get medical attention immediately

SKIN CONTACT: Immediately flush skin with water for 20 minutes. Remove and launder contaminated clothing before use.

INHALATION: Remove victim to fresh air. Administer artificial respiration if breathing ceases. Get medical attention immediately.

INGESTION: Do not induce vomiting. Give lots of water, if conscious. Get medical attention immediately.

SECTION VI - REACTIVITY INFORMATION

Aqua Pro

STABILITY: Stable

REACTIVITY: None will occur

HAZARDOUS DECOMPOSITION INGREDIENTS: As with any organic material, CO AND CO₂ may be expected as by-products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII - SPILL, LEAK AND DISPOSAL PROCEDURES

SMALL SPILLS: Absorb with an inert material such as sand or Vermiculite and sweep up and dispose of in accordance with federal, state, and local regulations.

LARGE SPILLS: Absorb with and inert material such as sand or Vermiculite and sweep up and dispose of in accordance with federal, state, and local regulations.

DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

SECTION VIII - SPECIAL PROTECTIVE EQUIPMENT

EYE AND FACIAL: None required under normal conditions.

SKIN: None required under normal conditions.

RESPIRATORY: None required under normal conditions.

VENTILATION: Local mechanical ventilation to keep TLV'S below recommended levels.

OTHER: None required under normal conditions.

SECTION IX - SPECIAL PRECAUTIONS

STORAGE: Store in cool, dry, well-ventilated place.

HANDLING: No special needs.

LEGEND: ND, Not Determined; N/A Not Applicable; NA, Not Available.

NOTICE

All information appearing herein is based upon data obtained from chemical manufacturers and or recognized technical sources. While the information is believed to be accurate, Snyder Manufacturing Corporation makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Snyder Manufacturing Corporation's control and therefore users are responsible for and assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process