


Color Enhancer

Seals and Enhances in One Application.

- V.O.C. Compliant
- Adds Natural Color to Honed, Flamed, Unpolished, Sandblasted Natural Stones, Slate, Brick and Pavers
- Long-Lasting Protection From Water and Oil Spills
- Designed to Permanently Increase Natural Color



STONE PRO

866.786.6310

www.stoneproonline.com



Product Description: A unique solvent-based, V.O.C. compliant impregnator sealer, which penetrates grout, stone and masonry surfaces to protect against water and oil staining while allowing substrate to properly breath. Non-yellowing, long-lasting. Will add natural color enhancement.

Coverage: Product will cover approximately 200 to 1,000 ft.² per gallon dependant on porosity of stone. Two coats are recommended for optimum performance. Allow to cure for a minimum of 24 hours between coats and after 72 hours, fully cured.

Directions: Always test product in an inconspicuous area to test suitability for intended use. Surface must be sound, thoroughly clean and free from waxes, sealants or coatings of any kind. For best results, use Stone Pro's Formula 51 stripper before applying Color Enhancer. Apply product evenly using a low-pressure sprayer or lamb's wool applicator. Do not dilute in any way. Please wipe off any excess residue after applying each coat. Excess residue may become slippery.

Caution: Combustible. Keep away from heat, open flame, sparks and/or any possible ignition source. Keep work area well ventilated. Gloves and goggles should be worn at all times. Respirator suggested in larger areas or non-ventilated areas. Read directions and other cautions on back of container before use of this product.

SECTION I - COMPANY & PRODUCT IDENTIFICATION

Color Enhancer

TRADE NAME: Stone Pro Color Enhancer/Sealer PRODUCT CODE: N/A
CHEMICAL NAME: Hydrocarbon blend CAS #: Mixture, no single CAS # applies
DATE: September 5, 2003

SECTION II - COMPOSITION FORMULA - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	%	CAS #	TLV (UNITS)	PEL
Aliphatic Petroleum Distillates	<50	64742-88-7	100 ppm	100 ppm

SECTION III - HAZARDS IDENTIFICATION

PERMISSIBLE EXPOSURE LEVEL: Undetermined

EYES: May cause mild eye irritation.

SKIN: May cause mild skin irritation.

INHALATION: Breathing small amounts of this material during normal handling is not likely to cause harmful effects.

INGESTION: Swallowing small amounts of this material during normal handling is not likely to cause harmful effects.

THIS MATERIAL IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA

SECTION IV - FIRST AID MEASURES

EYE CONTACT: Flush with water for 15 minutes lifting eyelids. Get medical attention.

SKIN CONTACT: Immediately flush skin with water for 15 minutes. Remove and launder contaminated clothing before use.

INHALATION: Remove victim to fresh air. Administer artificial respiration if breathing ceases. Get medical attention immediately.

INGESTION: Do not induce vomiting. Call physician or transport to an emergency medical facility.

SECTION V - FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT: 142 – 150 deg. F.

EXPLOSIVE LIMITS: LOWER: 1.0 UPPER: 6.0

FIRE/EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground or be moved by air and ventilation and ignited at a distant source.

EXTINGUISHING MEDIA: Foam, CO₂, dry chemical

FIRE FIGHTING PROCEDURES: Fire fighters should wear self-contained breathing apparatus with a full-face piece operated in the positive pressure demand mode and full protective clothing. Use water spray to cool nearby containers and structures.

HMIS HAZARD CLASS: Health =1 Flammability =2 Reactivity =0 Other =NA

Ranking: 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme

SECTION VI - ACCIDENTAL RELEASE PROCEDURES

SMALL SPILLS: Absorb liquid on vermiculite, floor absorbent or other absorbent material.

LARGE SPILLS: Eliminate all ignition sources. Prevent run off to drains or any bodies of water. Pump or vacuum material to containers for recovery. Absorb remaining material.

SECTION VII - HANDLING & STORAGE

Color Enhancer

STORAGE: Keep cool and dry. Empty containers may contain fumes. All hazard precautions on this data sheet should be taken when handling empty containers.

HANDLING: Sudden release of hot organic chemical vapors may result in ignition without the presence of obvious ignition sources.

2)

SECTION VIII - EXPOSURE CONTROL/PERSONAL PROTECTION

EYE AND FACIAL: Wear chemical splash goggles.

SKIN: Wear resistant gloves such as nitrile rubber.

RESPIRATORY: Wear NIOSH approved respirator in presence of mists and dusts.

VENTILATION: Local mechanical ventilation to keep TLV'S and PEL below recommended levels

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: F 355

SOLUBILITY: Insoluble pH: No data

PERCENT VOLATILE: 40% VAPOR DENSITY: 5.48 VAPOR PRESSURE: .500 mmHg

EVAPORATION RATE (BUTYL ACETATE=1): 151 (Ether) SPECIFIC GRAVITY: .80 @60 deg F.

APPEARANCE & ODOR: Clear liquid with solvent odor. VOC: 320 g/l

SECTION X - STABILITY & REACTIVITY INFORMATION

STABILITY: Stable

REACTIVITY: N/A

HAZARDOUS DECOMPOSITION INGREDIENTS: CO₂, CO, and phosphorous compounds.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION XI - TOXICOLOGICAL INFORMATION

No toxicological information has been generated for this material

SECTION XII - ECOLOGICAL INFORMATION

This product has never been found to present any environmental or ecological problems. Use according to the instructions. Dispose of in a sanitary manner.

SECTION XIII - DISPOSAL CONSIDERATION

Dispose in accordance with federal, state and local regulations.

SECTION XIV - TRANSPORT INFORMATION

DOT INFORMATION- 49CFR 172.101:

DOT DESCRIPTION: Petroleum Distillates, N.O.S., Combustible Liquid, UN1268, III

NOS Component: Naphtha

SECTION XV - REGULATORY INFORMATION

Color Enhancer

U.S. Federal Regulations:

TSCA – Intentional ingredients are listed; CERCLA RQ-40CFR 302.4 (a) – None listed; SARA 302 Components 40 CFR 355 Appendix A – None; Section 311/312 Hazard Class-40CFR 370.2 – Immediate (X) Delayed () Fire (X) Reactive () Sudden release of pressure (); SARA 313 Components 40CFR 372.65 – None; OSHA Process Safety Management 29CFR1910 – None listed; EPA Accidental Release Prevention 40CFR68 – None listed.

International Regulations:

ACOIN (Australia), DSL (Canada), ECL (South Korea), & EINECS (Europe) – Intentional ingredients are listed.

State & Local Regulations:

California Prop 65 - None

(3)

SECTION XVI - OTHER INFORMATION

Refer to product label for directions and any other cautions.

LEGEND: ND, Not Determined; N/A Not Applicable; NA, Not Available.

NOTICE

All information appearing herein is based upon data obtained from chemical manufacturers and or recognized technical sources. While the information is believed to be accurate, Snyder Manufacturing Corporation makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Snyder Manufacturing Corporation's control and therefore users are responsible for and assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.